

MastaFix20

3-IN-1 CEMENT



TECH DATA

MastaFix20 is a versatile 3-in-1 plaster based cement with a setting time of 20 minutes.

Ideal for patching and fixing cornices, MastaFix20 also performs well as a bedding cement ideal for small jobs, such as maintenance and prepaint repairs.



Performance

Mixing

Mixes easily by hand to a creamy gauge.

Body and Grab

Good body with fast and strong grab.

Workback

Partially set product can be reworked and used again to deliver a polished finish for mitres. Easy to straight stop and clean.

Setting

An even and gradual 20 minute set that can be accelerated to as little as 5 minutes by extended mixing.

Sustainable

Low VOC meeting sustainable building project requirements.

Benefits

- > For patching, cornice and jointing
- > Sets quickly
- > Easy to work with

Product Information

SIZE	10kg paper bag		
TYPE	Setting powder cement		
MIXING RATIO	1L of water to 2kg of MastaFix20		
WORKING TIME	15 – 20 minutes		
SETTING TIME	20 minutes	<input checked="" type="checkbox"/> Adjustable	
SYSTEM USAGE	<input checked="" type="checkbox"/> Cornice	<input checked="" type="checkbox"/> Patching	<input checked="" type="checkbox"/> Jointing
	<input checked="" type="checkbox"/> Standard systems	<input checked="" type="checkbox"/> Wet area systems	
VOC	<50g/L as VOC content per coating		

MastaFix20

3-IN-1 CEMENT

KNAUF

TECH DATA

Application

- Always use clean tools and containers.
- Pour the required amount of clean tap water into a container. Add the powder into water, mixing continuously to a smooth, thick consistency. Soaking is not recommended. Over mixing will accelerate the setting time.
- Only mix enough cement to be used in 15 minutes, and do not contaminate with previously mixed batches. Once the material starts to set it cannot be remixed.
- MastaFix20 will accept most types of decorative finishes. In accordance with AS/NZS 2311 *Guide to the painting of buildings*, a three coat paint system must be used. This consists of a sealer/undercoat and two coats of paint.

Optimise product performance by:

- Storing in a dry, well ventilated environment fully protected from the weather.
- Washing tools before product dries and hardens.
- Ensuring MastaFix20 does not dry out before setting has taken place under severe hot dry conditions.



Quality
ISO 9001

SAI GLOBAL

Knauf products manufactured in Australia are produced in accordance with quality systems certified as complying with AS/NZS ISO 9001:2008.

Warranty

Knauf's products are guaranteed by a 10 Year Warranty. Visit knaufplasterboard.com.au for details.

Technical Advice

For technical advice, please call Knauf technical services on **1300 724 505**.